

Stream editor and regular expressions

Security (CT0657) 2026-27
Università Ca' Foscari Venezia

Riccardo Focardi

<https://www.unive.it/people/focardi>
secgroup.dais.unive.it



Università
Ca' Foscari
Venezia

Stream editor sed

sed is a simple but powerful Unix tool to **filter** and **transform** text

sed is invoked as **sed SCRIPT INPUTFILE ...**

Example: replace hello with world in file input.txt

sed 's/hello/world/' input.txt	(output goes to stdout)
sed -i 's/hello/world/' input.txt	(in-place, modifies input.txt)

The following commands are equivalent:

sed 's/hello/world/' input.txt	> output.txt	
sed 's/hello/world/' < input.txt	> output.txt	
cat input.txt sed 's/hello/world/' -	> output.txt	(with or without -)

sed commands

A sed **script** consists of one or more sed commands

sed commands follow this syntax:

[**addr**]**X**[**options**]

- **X** is a single-letter sed command
- [**addr**] line address: single line number, regexp, or range of lines
- [**options**] for some commands

Delete: command **d** deletes lines

sed '**1d**' input.txt : deletes first line

sed '**1,3d**' input.txt : deletes first three lines

Print: command **p** prints lines

sed '**1p**' input.txt : prints first line

NOTE: line is printed twice

Examples

```
$ sed '1d' test.txt  
line 2  
line 3  
line 4
```

```
$ sed '1,3d' test.txt  
line 4
```

```
$ sed '1p' test.txt  
line 1  
line 1  
line 2  
line 3  
line 4
```

Command line option **-n** tells sed not to print lines unless they are printed explicitly

Example:

```
$ sed -n '1,2p' test.txt  
line 1  
line 2
```

Substitution

Command **s** substitutes strings

```
sed 's/hello/hi/' input.txt
```

By default substitution happens **once**
for each line

```
$ cat input.txt  
hello guys hello everyone
```

```
$ sed 's/hello/hi/' input.txt  
hi guys hello everyone
```

Option **g** makes substitution global

```
$ sed 's/hello/hi/g' input.txt  
hi guys hi everyone
```

Option **i** makes search case
insensitive and a number specifies
which occurrence should be replaced

```
$ sed 's/HELLO/hi/i2' input.txt  
hello guys hi everyone
```

Substitution (more examples)

It is possible to use a **custom separator** with substitution command

```
sed 's:hello:hi:' input.txt
```

As for d and p, it is possible to indicate which **lines** should be examined:

```
sed '2,3s/line/LINE/' test.txt
```

only applies to lines 2 and 3

Only **print** rows that match string:

```
sed -n '/hello/p' input.txt
```

Delete rows that match string:

```
sed '/hello/d' input.txt
```

Apply a **mapping**:

```
sed 'y/abc/ABC/'
```

replaces each occurrence of a,b,c with A, B, C, respectively.

Regular expressions

Regular expressions are **patterns** representing sets of strings

Useful to perform **advanced searches** in which it is necessary to find strings with a particular **structure**

Programs **grep** and **sed** both support regular expressions

^ is the beginning of line

Example: `ls -al | grep '^d'`

matches all **directory** files in the current directory (**d** is the flag that indicates a directory file)

If we omit the **^** symbol, grep will match all lines containing a d, not necessarily in the first position

Regular expressions (2)

\$ indicates end of the line

. represents a single character

Example: `grep '.ino'` will match names such as Nino, Pino, Gino, ...

c* represents a possibly empty, arbitrary number of occurrences of character c

Example: `grep 'smart *card'`

(smartcard, smart card, smart card, ...)

.* matches an arbitrary number of arbitrary characters

c\+ one or more occurrences of c

c\? zero or one occurrences of c

Notice that + and ? need to be **escaped** prepending a backslash \ character

Regular expressions (3)

Note on **escaping**:

- To find a special character like `.` or `*` it is enough to **escape** it with a backslash `\` character
- For characters that needs to be escaped in regular expression such as `\+` and `\?` it is instead enough to **remove the backslash**

`[0123456789]` or `[0-9]`

represents all digits from 0 to 9

Example: `[0-9]\+`

a decimal number of arbitrary length

`[^0-9]` anything that is **not** a digit

Example: `grep '^[^0-9]*$'`

all lines that do not contain digits

Classes

[[:alnum:]] Alphanumeric [a-z A-Z 0-9]

[[:alpha:]] Alphabetic [a-z A-Z]

[[:blank:]] Blank characters (spaces or tabs)

[[:cntrl:]] Control characters

[[:digit:]] Numbers [0-9]

[[:graph:]] Printable characters (excluding spaces)

[[:lower:]] Lowercase letters [a-z]

[[:print:]] Printable characters (including spaces)

[[:punct:]] Punctuation characters

[[:space:]] Spaces (including \t \n)

[[:upper:]] Uppercase letters [A-Z]

[[:xdigit:]] Hex digits [0-9 a-f A-F]

Regular expressions in sed

sed supports regular expressions

For substitutions, it is useful to **refer** to the matched text. This can be done in two ways:

& is substituted with the **whole** matched string

Example: add world after hello
sed 's/hello/**&** world/g'

Back references and brackets: refer to portions of the matched text

Ex.: extract the name from a mail

```
's/Dear \([^ ]*\) .*$/Name = \1/g'
```

Notice that the pattern we refer to is surrounded by **\(** and **\)**, while the reference to it is **\1**

Use **\2**, **\3**, ... for next references

Exercises

Files for exercises are available:

- at /home/rookie/Shell/ in the [testbed](#) host
- as a [zip file](#)

Exercise 1: pretty printing

Given a list of telephone numbers of the form **123456789** use **sed** to rewrite them as **(123)456-789**

Anything in the wrong format should be **left unmodified**.

```
$ cat numeri.txt
```

```
123456789
```

```
392948291
```

```
321582923
```

```
321904984
```

```
Not a number
```

```
hello
```

```
$ sed ... numeri.txt
```

```
(123)456-789
```

```
(392)948-291
```

```
(321)582-923
```

```
(321)904-984
```

```
Not a number
```

```
hello
```

Exercise 2: break ROT13

The following text (rot.txt file) has been encrypted by replacing each letter with the one 13 positions ahead in the alphabet (modulo 26) aka [ROT13](#)

Break it with **sed**!

Hint: Check out command **y**

```
jryy qbar thlf, lbh oebx r n  
pvcure jvgu frq!
```

Exercise 3: filename conversion

Use sed to select and convert all file names with suffix `.html` given as output by `ls` into **capital letters** with suffix `.HTM`

Non-matching files should be **omitted**

Hint 1: Check out command **y**

Hint 2: You can concatenate commands as: `sed 'cmd1;cmd2'`

Hint 3: Use blocks `{...}` with an address: `sed -n '/\.html$/{...;p}`

```
$ ls
document.pdf
myPage.html
test.html
```

```
$ ls | sed ...
MYPAGE.HTM
TEST.HTM
```

Exercise 4: data extraction

Use **sed** to extract full user names (5th field) from **/etc/passwd/**

NOTE: fields are separated by :

```
$ sed ... /etc/passwd
root
daemon
bin
...
Mailing List Manager
ircd
Gnats Bug-Reporting System (admin)
nobody
systemd Network Management
```

Extra: GNU extensions

There are some handy GNU extensions that allows for shorter regexps (do not work in BSD unix)

`c\{n\}` repeats `c` `n` times

Example:

`[[:digit:]]\{10\}`

is a 10 digits number

`\L` and `\U` in `s` commands convert to lowercase and uppercase, respectively

Example:

```
$ cat input.txt  
hello guys hello everyone
```

```
$ sed 's/hello/\U&/g' input.txt  
HELLO guys HELLO everyone
```